



Article : 930004

Product : PTFE

Description

High-quality universal lubricant for treating mechanical parts of metal and plastic. PTFE spray has a very low coefficient of friction, a fine texture (particle size approximately 5 micrometres) and a good adhesion. PTFE spray is resistant against weather influences and weak acids and alkalis, is water-repellent and pH neutral. It prevents wear and jamming. PRO-Tech PTFE Spray can withstand temperatures from -50°C to + 250°C.

Specifications

- ❖ Packaging : 400ml NET
- ❖ Base : Mineral oils, PTFE and additives
- ❖ Appearance : Light, slightly murky yellow liquid
- ❖ Propellant:Propane-Butane
- ❖ VOC-CH %:40%
- ❖ VOC-EU g/l:297 g/l
- ❖ Specific gravity (g/ml 20°C):0.735
- ❖ Vapour pressure at 20°C:2.8-3.2 bar
- ❖ Spraying flow rate:2.5 g/sec
- ❖ Temperature resistant : -50°C to +250°C
- ❖ pH value : Neutral
- ❖ Distribution : 1 box of 12 products
- ❖ Multidirectionnal



Instructions for use

The aerosol can should be at room temperature. The ideal processing temperature is from 5 to 30°C. Shake the aerosol can before use. Apply the PTFE oil in a thin layer. The best lubrication is obtained after evaporation of the solvent (approximately 1 minute).

Application

- ❖ Chains
- ❖ Sprockets
- ❖ Hinges of doors
- ❖ Industrial vacuum pumps
- ❖ Guide rails
- ❖ Conveyor belts
- ❖ Guide rails sliding doors
- ❖ Hinges and locks
- ❖ (Agricultural) machinery
- ❖ Rubber Sealing profiles
- ❖ Planers
- ❖ Saw benches

General condition

For optimal performance, it should be applied to a clean dry surface at a temperature between 5°C and 30°C.

Must be kept in a frost-free place.

Stored as given above, the average storage period is approximately one year.

Avoid exposure to temperatures above 50°C and keep away from sources of ignition, heat and sunlight.

As with all handling and storage operations, NO SMOKING is very strongly recommended.

The SOPPEC PRO TECH ranges offer a wide choice of products in aerosol format, grouped according to function: PROTECTION, CLEANING, LUBRICATION !

SOPPEC ZI NERSAC
16440 NERSAC
FRANCE
Tel : +33(0)5 90 93

Distribué par :
Distributed by :

TECHNIMA CENTRAL GmbH
KREUZERWEG 13
77955 ETTENHEIM
ALLEMAGNE
Tel : + 49-(0) -7822-789 00 11

CIA TECHNIMA SUD EUROPA SRL
VIA S. BRIGIDA N.43
10060 ROLETTA (TO)
ITALIE
Tel : +39 0121 542 542

TECHNIMA NORDIC AB
KROKSLÄTTS TORG 5
431 37 MÖLNDAL,
SUEDE
Tel : +46 (0)31 10 21 90