



Article: 930105 Product: Vaseline

# **Description**

PRO-Tech Vaseline spray is a high-quality, transparent universal lubricant and protective agent against corrosion, wear and jamming of components. For maintenance and protection of metal, bolts and nuts, hinges and battery terminals etc. The product is used a lot in antenna construction and communication engineering. Excellent anti-corrosive properties and resistant to salt, weak acids and alkalis. PH neutral and Water-repellent.

# **Specifications**

- ❖ Contents: 400 ML NET
- Base: Pure premium Vaseline, not acid, non-resinous white Vaseline
- Appearance: Light, slightly murky colourless liquid
- Propellant: Propane-Butane
- ❖ VOC-CH %:93%
- ❖ VOC-EU g/I:594 g/I
- Specific gravity (g/ml 20°C):0.642
- ❖ Vapour pressure at 20°C:3.3 3.9 bar
- Spraying flow rate:1.1 g/sec
- Dropping point:50°C-56°C
- Distribution: 1 box of 12 products

### **General condition**

For optimal performance, it should be applied to a clean dry surface at a temperature between  $5^{\circ}\text{C}$  and  $30^{\circ}\text{C}$ .

Must be kept in a frost-free place.

Stored as given above, the average storage period is approximately one year.

Avoid exposure to temperatures above 50°C and keep away from sources of ignition, heat and sunlight.

As with all handling and storage operations, NO SMOKING is very strongly recommended.



#### Instructions for use

The aerosol can should be at room temperature. The ideal processing temperature is from 5 to 30°C. Shake the aerosol can before use. Apply the Vaseline spray in a thin layer. The best lubrication is obtained after evaporation of the solvent (approximately 1 minute).

### **Application**

- Protection of 'ultralight' material
- Panels of audio equipment
- Antenna construction
- Communication engineering
- Cable terminals
- Socket connectors
- Sliding surfaces
- Electrical contacts

The SOPPEC PRO TECH ranges offer a wide choice of products in aerosol format, grouped according to function: PROTECTION, CLEANING, LUBRICATION!

SOPPEC ZI NERSAC 16440 NERSAC FRANCE Tel:+33(0)5 90 93 Distribué par : Distributed by : TECHNIMA CENTRAL Gmbh KREUZERWEG 13 77955 ETTENHEIM ALLEMAGNE Tel : + 49-(0) -7822-789 00 11 CIA TECHNIMA SUD EUROPA SRL
VIA S. BRIGIDA N.43
10060 ROLETTA (TO)
ITALIE
Tel: +39 0121 542 542

TECHNIMA NORDIC AB KROKSLÄTTS TORG 5 431 37 MÖLNDAL, SUEDE Tel: +46 (0)31 10 21 90