Technical Datasheet



3M[™] Industrial Safety Helmet G2000

Product Description

The 3M[™] Industrial Safety Helmet G2000 is designed to offer reliable head protection. The low profile shape and low back gives good coverage and the optional ventilation holes provide additional comfort for the wearer. The G2000 is available with a market proven ratchet providing easy adjustment for the comfort of each user. A wide range of accessories is available for additional protection and functionality.

Key Features

- Uvicator indicates when it is time to replace the helmet due to UV exposure
- · Ventilated versions available for increased comfort
- Flat front surface suitable for attaching a brand name or logo
- · Replaceable leather or plastic sweatband
- · Extended back edge for increased coverage
- Electrical insulated version available tested according to EN50365
- Approved for use at -30°C
- · Wide range of accessories available
- Compatible with a wide range of 3M[™] Peltor[™] Hearing Protection

Applications

- Industry
- Construction
- Forestry
- Electrical work

Testing and Approval

The 3M[™] Industrial Safety Helmets G2000 meets the requirements of the PPE Directive (89/686/EEC) and are thus CE marked. The product has been tested and approved by SP, Swedish National Testing and Research Institute, Box 857 SE-501 15 Borås Sweden (Notified body number 0402).

The product has been tested and approved in accordance with EN 397:1995, EN 397:1995/A1:2000 and certain versions of the G2000 in accordance with EN 50365:2002.

Accessories

- · GH2 Chinstrap
- HYG3 Sweatband plastic (standard)
- HYG4 Sweatband leather
- G2E Band for six point harness
- GR3C Rain shield
- · GLF Lamp and cord holder
- · GLF-B Safety glasses holder
- V6* Integrated eyewear
- V4* Safety visors, see separate sheets
- FP8228/1 Reflex kit (4 pcs)



Materials

Component	Material		
Shell	UV stabilized ABS		
Headband	LDPE		
Cradle	Polyester		
Sweatband	Leather or synthetic		

Use limitation

- Never modify or alter the safety helmet
- Do not use this safety helmet against hazards other than those specified in the user instruction.
- Use, store and maintain the safety helmet in accordance with the user instruction.

Weight

Safety helmet G2000 incl. standard fitting G2M weighs 380g.

Use and storage

Temperature range for usage	-30°C - +55°C			
Recommended storage conditions	+3°C - +40°C, <85% humidity			
Maximum recommended shelf life	2-5 years depending on the work environment and usage conditions			

Product Configuration

Helmet Shell

G2000	With ventilation
G2001	Without ventilation

Fitting Sizes

Pinlock Harness	54-62cm
Ratchet Harness	53-62cm

Suspension

G2C	4 Point Pinlock headband with synthetic sweatband
G2D	4 Point Pinlock headband with leather sweatband
G2E	Additional six point suspension strap
G2M	4 Point Ratchet headband with leather sweatband
G2N	4 Point Ratchet headband with plastic sweatband

Product Classification

Additional Protection Characteristics

Low Temperatures	-10°C	1	-20°C	1	-30°C	√
Electrical Properties	440Vac*	✓	EN50365*	✓		
High Temperatures	+50°C	✓	+150°C	×	Molten Metal	✓
Lateral Deformation	LD	✓				

Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

Product Range





3M Deutschland GmbH Carl-Schurz-Straße 1 41453 Neuss Tel.: +49 (0) 2131 14 26 04

Fax: +49 (0) 2131 14 32 00 E-Mail: arbeitsschutz.de@mmm.com Web: www.3Marbeitsschutz.de 3M (Schweiz) GmbH Eggstrasse 93 8803 Rüschlikon Tel.: +41 (0) 44 724 91 51 Fax: +41 (0) 44 724 94 40

Tel.: +41 (0) 44 724 91 51 Fax: +41 (0) 44 724 94 40 E-Mail: arbeitsschutz-ch@mmm.com Web: www.3Marbeitsschutz.ch 16029 3M is a trademark of 3M company. Please recycle. Printed in UK. © 3M 2012. All rights reserved 3M.

3M Österreich GmbH Kranichberggasse 4 1120 Wien Tel.: +43 (0) 1 86 686 541 Fax: +43 (0) 1 86 686 229 E-Mail: arbeitsschutz-at@mmm.com Web: www.3Marbeitsschutz.at