

EU Type Examination Certificate

Date: 2021/08/31

n. **929213503/OE**

Validity: 2026/02/08

This Certificate cancels & replaces the previous one n° 906210603/OE dated 2021/02/09.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	OREGON TOOL GmbH Lise-Meitner-Straße 4 – 70736 Fellbach – Germany	
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials) + EN ISO 17249:2013 against mechanical chainsaw cutting	
Category of PPE:	III : "severe" risks. the certificate shall be reconfirmed by the annual surveillance (module C2)	
Model	"XX73125" KOX TRE	
Description:	  <p><u>model</u>: C (half-knee boot); <u>fastening system</u>: by means of laces; <u>processing</u>: ago; <u>sole</u>: black rubber VIBRAM FURÀ declared antistatic and oil-resistant, with yellow stamp and rand made of black rubber "Ilga" with height of about 3 cm on the whole circumference and four spikes in the plantar arch area; <u>midsole</u>: black and red microporous material (DAVOS); <u>upper</u>: red suede water resistant leather "Perwanger", declared thickness 2,2-2,4 mm (PWNR), with cut-resistance insert made of 8 layers of white fabric "Engtex"; <u>collar</u>: black leather declared thickness 1 mm (RNCD), coupled with foam material, with black rear comb-over made of Lycra (LVG); <u>tongue/bellows</u>: black leather declared thickness 1 mm (RNCD), lined, centrally padded and reinforced with the red suede water resistant leather "Perwanger", declared thickness 2,2-2,4 mm (PWNR); <u>vamp and quarter lining</u>: grey fabric EVENT coupled with membrane PTFE, which also covers the insole; <u>upper tongue and collar lining</u>: black leather declared thickness 1 mm (RNCD); <u>insole</u>: white multi-layered fabric Texon Enigma Zero HT2 which also serves as penetration resistant insert, coupled with white rigid polymeric insole; <u>removable insock</u>: grey foam material (PTS SECAL) coupled with grey knitting in contact with the foot, and grey fabric in the lower part, with heel seat lining covered by black knitting applied in the lower area; <u>toecap</u>: varnished steel, SMAL art. 2443.</p>	
Technical Standard:	EN ISO 20345:2011 EN ISO 20344:2011 EN ISO 17249:2013	Personal protective equipment – Safety footwear Personal protective equipment – Test methods for footwear Safety footwear with resistance to chain saw cutting
Intended use:	woodcutters, forest rangers, farmers and alike (foot protection for works implying the use of a chainsaw)	
Size range:	from 38 to 48	

EU Type Examination Certificate

Date: 2021/08/31

n. **929213503/OE**

Validity: 2026/02/08

Technical File: **DC-13874/E**

Test report: **RCT n°4033014/E**

Functions and performance levels: **basic requirements for safety footwear (SB)** (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

SRC (*) = Slip resistance – meets the following requirements:

- surface: ceramic / lubricant: detergent solution;
- surface: smooth steel / lubricant: glycerine.

(*) the final level of the anti-slip features is achieved after the first hours of trial stage.

Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):

S3 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; **HRO** = resistance to hot contact of the outsole; **CI** = cold insulation of the outsole; **WR** = resistance to water penetration of the whole footwear.

Furthermore the footwear meets the requirements for footwear with resistance to chain saw cutting (see **EN ISO 17249:2013**) – **LEVEL: 3** (chain speed: 28 m/s).

Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).

Marking:



LEV 3 28 M/S

On a label stitched onto the tongue and including the following information:

- **CE Marking** + number of the Notified Body in charge of the annual control of the PPE;
- registered Trademark (KOX) + name and complete address of the Manufacturer;
- identification of the product (alphanumeric article code) + country code (D);
- size of the footwear;
- month and year of production;
- nr./year of the two Technical Standards of reference + safety symbols;
- pictogram referred to the EN ISO 17249 with indication of the level reached (on the external side of the footwear);
- additional info: batch number, "made in...".



EU Type Examination Certificate

Date: 2021/08/31

n. **929213503/OE**

Validity: 2026/02/08

KOXX 42

Lotto 110

XX73125 06/21

D CE 0498

EN ISO 20345:2011

S3-WR-CI-HRO-SRC

EN ISO 17249:2013

Made in Romania

Oregon Tool GmbH

Lise-Meitner-Strasse 4

70736 FELLBACH

DEUTSCHLAND



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

