TEST REPORT



Measuring tape Spencer Super 15m, 20m and 25m

Test no. 0800

OWNER OF TEST CERTIFICATE

Grube KG Forstgerätestelle Hützeler Damm 38 D - 29646 Bispingen

www.grube.de



Results and assessments

Results from the 1986 field study

Measuring tape: Spencer Super 15m, 20m and 25m Grube KG Forstgerätestelle, Hützeler Damm 38; 29646 Bispingen

Field of application

Length measurement of long and short timber

Feature	Result
Handling	Simple, spring preload enables good extension and retraction of the measuring tape. Very good winding quality in good conditions. Wire claw or tilting hooks ensure a secure hold in the wood.
Measuring tape	Spring steel tape with markings on both sides. Easy to recognise, centime- tre graduation with decimetre and metre markings (red) on a yellow back- ground.
Maintenance	Measuring tape guide open at the side. This makes it slightly more dirty, but also easier to clean and maintain. Easy to replace, but requires practice.

Version

Light metal housing with spring encapsulated in the housing, replaceable tape measure, wear piece riveted on with rubber stopper.

Dimensions and weights

Execution	15 m	20 m	25 m
Case diameter	102 mm	102 mm	102 mm
Height	43 mm	43 mm	43 mm
Weight	510 g	600 g	690 g

This report is based on practical tests and measurements carried out by professional users according to the specifications of the Expert Committee on Equipment and Tools of KWF e.V.

Test completion December 2023 KWF Services GmbH Approval until December 2028 Spremberger Straße 1
First approval April 1986 64823 Groß-Umstadt
E-Mail: info@services.de Phone: 06078-785-28

Internet: <u>www.kwf-services.de</u>